



P.C.B PATTERN

ORDER INFORMATION
NR08 - P - HXX - XX

Series | Base Height | No. of pos

P : Plug
S : Socket

	A	B	C	D		A	B	C	D
8P	5.1	2.4	4.2	3.86	34P	15.5	12.8	14.6	14.26
10P	5.9	3.2	5.0	4.66	36P	16.3	13.6	15.4	15.06
12P	6.7	4.0	5.8	5.46	38P	17.1	14.4	16.2	15.86
14P	7.5	4.8	6.6	6.26	40P	17.9	15.2	17.0	16.66
16P	8.3	5.6	7.4	7.06	42P	18.7	16.0	17.8	17.46
18P	9.1	6.4	8.2	7.86	44P	19.5	16.8	18.6	18.26
20P	9.9	7.2	9.0	8.66	46P	20.3	17.6	19.4	19.06
22P	10.7	8.0	9.8	9.46	48P	21.1	18.4	20.2	19.86
24P	11.5	8.8	10.6	10.26	50P	21.9	19.2	21.0	20.66
26P	12.3	9.6	11.4	11.06	60P	25.9	23.2	25.0	24.66
28P	13.1	10.4	12.2	11.86	70P	29.9	27.2	29.0	28.66
30P	13.9	11.2	13.0	12.66	80P	33.9	31.2	33.0	32.66
32P	14.7	12.0	13.8	13.46	100P	41.9	39.2	41.0	40.66

HIGH	PLUG(H)	SOCKET(H)
4.0	1.0	3.0
4.5	1.0	3.5
5.0	1.0	4.0
5.5	1.0	4.5
6.0	2.0	4.0
6.5	2.0	4.5

△		THROUGH HOLE	UNIT	SCALE	TOLERANCE
△		PROJECTION	mm	1/5	
△		APPROVAL CHECK		DESIGN	DRAW
△					
MARK	DATE	REVISION	SIGN		
	2025				
			W/ NAME	0.8mm PLUG	
			P/ NAME	0.8mm BOARD TO BOARD	
			DRAWING NO.	NR08-P	