



ORDER INFORMATION
 NR05 - P - HXX - XX
 Series | Base Height | No. of pos

P : Plug
 S : Socket

HIGH	PLUG(H)	SOCKET(H)	F
3.0	0.8	2.2	1.6
3.5	1.3	2.2	1.6
4.0	1.0	3.0	1.9
4.5	1.0	3.5	1.9
5.0	1.0	4.0	1.9
5.5	1.0	4.5	1.9
6.0	2.0	4.0	1.9
6.5	2.0	4.5	1.9

	A	B	C	D	E
8P	4.70	1.50	2.40	3.40	2.00
10P	5.20	2.00	2.90	3.90	2.50
12P	5.70	2.50	3.40	4.40	3.00
14P	6.20	3.00	3.90	4.90	3.50
16P	6.70	3.50	4.40	5.40	4.00
18P	7.20	4.00	4.90	5.90	4.50
20P	7.70	4.50	5.40	6.40	5.00
22P	8.20	5.00	5.90	6.90	5.50
24P	8.70	5.50	6.40	7.40	6.00
26P	9.20	6.00	6.90	7.90	6.50
28P	9.70	6.50	7.40	8.40	7.00
30P	10.20	7.00	7.90	8.90	7.50
32P	10.70	7.50	8.40	9.40	8.00
34P	11.20	8.00	8.90	9.90	8.50

	A	B	C	D	E
36P	11.70	8.50	9.40	10.40	9.00
38P	12.20	9.00	9.90	10.90	9.50
40P	12.70	9.50	10.40	11.40	10.00
42P	13.20	10.00	10.90	11.90	10.50
44P	13.70	10.50	11.40	12.40	11.00
46P	14.20	11.00	11.90	12.90	11.50
48P	14.70	11.50	12.40	13.40	12.00
50P	15.20	12.00	12.90	13.90	12.50
60P	17.70	14.50	15.50	16.40	15.00
70P	20.20	17.00	18.00	18.90	17.50
80P	22.70	19.50	20.50	21.40	20.00
90P	25.20	22.00	23.00	23.90	22.50
100P	27.70	24.50	25.50	26.40	25.00

MARK	DATE	REVISION	SIGN	THROWING PROJECTION	UNIT mm	SCALE	TOLERANCE
△	2012/05			APPROVAL		N/S	
△				CHECK		DESIGN	
△				DESIGN		DRW	

W NAME	PART NAME	DRWG. NO.
SH	0.5mm BOARD TO BOARD	NR05-P